

**Product Description**

**Astramax®**

HD-LED is a breakthrough technology with vastly better performance than standard definition LED or conventional surgical lights.



**Product Images**



**Product Features**

**Full Spectrum Colour Rendition**

The surgical lighting has near perfect colour rendition across the full visible spectrum.

- Easy to distinguish small differences in tissue
- All the colours are strong and vibrant
- Reduced eye strain by making the light do the work instead of the eye

**Red Balance Control**

With the highest R9 red colour rendition, Astramax HD-LED provides optimum visualisation of red tissues

- Enhanced visualisation of red tissues
- Improved differentiation between tissues of similar colour
- You can adjust the light colour to match your own optical colour response

**Fat Beam Illumination**

Higher light flux ensures bigger illuminated fields and more light across the full width of the illuminated area.

- High light intensity across the full illuminated area for uniform vision
- Avoids visual distraction by reducing high contrast in the illuminated area
- Adjust the beam size to suit your working area to eliminate peripheral distraction

**Slim, Compact and Powerful**

Ultra slim and light-weight lamp head enables smooth, fast and precise positioning during procedures. Astramax HD-LED is a compact yet powerful surgical light with an impressive 150,000 Lux output

**Economical Light with Long Life**

Astramax HD-LED provides exceptional performance at a competitive price with minimal running costs. Using less than 50 watts of power and with >60,000 hours of LED life which equates to more than 20 years of normal use, Astramax HD-LED continually saves money on energy and maintenance.

**Environmentally Friendly**

HD-LED lights use up to 70% less energy than conventional medical lighting. HD-LED lights have the highest lighting performance with the smallest energy consumption.

LEDs are also mercury free, do not contain CFCs, POPs, VOCs, halogens or other harmful chemicals and are ROHS compliant.

**Large Illuminated Area with Shadow Control**

A large illuminated area of up to 320mm diameter makes it easy to illuminate large areas of tissue to target the light onto the wound. By spreading the LEDs across the lighting surface, a much better distribution of light is provided from the lamphead. This enables excellent shadow control to under-light obstructions during procedures.

**Large Movement Range**

Astramax HD-LED lamp head is mounted on multimovement arm mechanisms. The lamp has 5 rotations to allow easy positioning of the light beam from any angle.

**Infection Control**

The lamp head is sealed to IP54 to protect from ingress of dirt and fluids. The smooth surfaces of the lamp head allow for easy disinfection. The lamp head is manoeuvred using a sterilisable handle.

*Images are representative of example system only - Mount styles vary depending on model  
Please refer to drawing layout for model appearance information*

*Please contact one of our Sales Team to discuss your requirements further*



ELMFIELD ROAD | MORLEY | LEEDS | LS27 0EL | WEST YORKSHIRE | UNITED KINGDOM. T: +44 113 277 7393 / 0845 1243 666 F: +44 113 272 8844 / 0845 1243 667  
E: enquiries@brandon-medical.com W: www.brandon-medical.com  
Brandon Medical Company Limited. Registered in England & Wales No. 2827189. VAT No. GB734 591421. A subsidiary of Brandon Group Limited.

Model Number	Description
AM30WJ	Astramax 30 Series Main Lamp (150kLux) Wall Mounted
AM30WOST	Astramax 30 Series Main Lamp (150kLux) Wall Mounted (Requires Separate External Transformer)

**Technical & Performance Information:**

Unless otherwise stated: All linear dimensions in mm, angles in degrees (±5°) and weights in kg

General System Information	AM30WJ	AM30WOST
Mount Type	Wall + Swing-Spring Arm	Wall + Swing-Spring Arm [Separate Transformer]
Lamphead 1	AM30	AM30
Weight (kg)	14.7	14.7
Conformity	CE (EU MDR 2017/745)	
Type of luminaire (to BS EN 60601-2-41)	Surgical Luminaire - Minor (Treatment)	
Medical Device Classification	I	
Electrical Classification	I	
Electrical conformity	BS EN 60601-1; BS EN 60601-2-41	
System Max Power [VA]	44	44
System Power Consumption @100% Intensity	37W	37W
Additional Information	-	Requires Separate Transformer

Mount Code	Wall + Swing-Spring Arm	Wall + Swing-Spring Arm [Separate Transformer]
Number of Arms	1 -	
Mounting Height [Wall Bracket Only]	2060	2060
Weight of Mount (Including Suspension Arms)	9.7	9.7
Arm 1 Lengths Horizontal/Suspension Arm [Total Radius] (mm)	800/750 [1550]	800/750 [1550]
Arm 1 Lateral Rotation of Horizontal about Central Stem Spindle (±5°)	180	180
Arm 1 Lateral Rotation of Spring Arm about Horizontal Spindle (±5°)	360	360
Suspension Arm Angle Max Vertical Adjustment Up (±5°)	45°	45°
Suspension Arm Angle Max Vertical Adjustment Down (±5°)	45°	45°
Power Supply Unit Type	50W 24V	Supplied Separately
Supply Voltage	100 - 240V AC 50/60Hz	100 - 240V AC 50/60Hz

Lamphead Photometric Data *	AM30	
Central Illuminance @ 1 metre (Lux max ±10%)	150,000	
Field Diameter D10 @ 1 meter (mm)	90 to 320 (Variable)	
Field Diameter D50 @ 1 meter (mm)	90-160	
Nominal Working Distance from Lamphead m	1	
Colour Rendition Ra (Av R1-R8)	≥95	
Colour Rendition R9 (red)	≥95	
Colour Temperature (°K)	4300° K	
Adjustable Colour (Red Balance) (°K)	3100° to 5000° K	
Number & Type of Lights per Lamphead	39 HD-LED®	
LED Life (Hours)	>60,000	
Comfort Halo @ 1m (mm)	N/A	
Radiant Energy	3.31mW/m <sup>2</sup> per Lux	
Solid State Focusing Control	Control via Handle	
Intensity Control	Control on Keypad	
Shadow-Less Light Technique	Multiple LED Elements	
Electronically Dimmable Light Intensity Range	5-100%	
Depth of Illumination (Without Refocusing)	L1/L2@60% (mm)	-
	L1/L2@20% (mm)	500
Infrared Content	-	
Temperature Increase in Surgeon's Head Area	<1°C	
Luminous Efficacy (lm/W)	-	

Lamphead General, Mechanical & Electrical Data*	AM30	
Removable Sterilisable Handle	Yes (Sterilisable at 137°C)	
Anti-Microbial Surfaces	Yes	
Light On/Off Switch Location	Keypad on Lamphead	
Ingress Protection Rating	IP54	
Lamphead Diameter (mm) Approx	480	
Lamphead Weight (kg) Approx	5	
Lamphead Pitch (°)	290°	
Lamphead Roll (°)	Unlimited 360°	
Lamphead Yaw (°)	N/A	
Power Supply Unit Requirements	50W 24V DC	
Power (VA)	Nominal [Max]	30.6 [44]
	Power Consumption (W)	Nominal [Max]
Keypad Orientation	Horizontal	

\*Data per Lamphead

See also Layout Drawing: BSD\_Astramax Wall Systems Layout [15003]

Images are representative of example system only - Mount styles vary depending on model  
Please refer to drawing layout for model appearance information  
Please contact one of our Sales Team to discuss your requirements further



ELMFIELD ROAD | MORLEY | LEEDS | LS27 0EL | WEST YORKSHIRE | UNITED KINGDOM. T: +44 113 277 7393 / 0845 1243 666 F: +44 113 272 8844 / 0845 1243 667  
E: enquiries@brandon-medical.com W: www.brandon-medical.com  
Brandon Medical Company Limited. Registered in England & Wales No. 2827189. VAT No. GB734 591421. A subsidiary of Brandon Group Limited.